

# Polara iNX Push button

## SPECIFICATIONS

<b>POWER</b>	10 to 24VDC
<b>PUSH BUTTON</b>	ADA compliant. Field adjustable directional arrow is standard; bidirectional and blank buttons available. Optional adjustable locator tone
<b>ACTIVATION CONFIRMATION</b>	Yellow LEDs and voice confirmation activated when push button is pressed; custom message available
<b>PUSH BUTTON HOUSING</b>	Yellow powder coat finish is standard; black and green available
<b>SPEAKER</b>	Field replaceable, weather resistant, 10-watt audio amplifier Maximum volume: 100 dB at 1 meter
<b>INSTRUCTIONAL SIGN</b>	9" x 12" is standard; larger signs available; braille available. Retroreflective sheeting with tamper-resistant mounting screws
<b>OPERATING FORCE</b>	Three adjustable settings: .5 to 3.5 pounds
<b>IDLE CURRENT DRAW</b>	~9mA @ 12 VDC
<b>PEAK CURRENT DRAW</b>	~500mA (@15VDC) with voice message at maximum
<b>ENCLOSURE</b>	NEMA 250 Type 4X Powdercoated cast aluminum cover and backplate
<b>CONNECTIVITY</b>	Bluetooth 5.0 Polara Field Service app for customization
<b>WIRING</b>	6 conductor
<b>OPERATING TEMPERATURE RANGE</b>	-30°F to 165°F (-34°C to 74°C)
<b>DIMENSIONS</b>	9"W x 18.2"L x 2.6"H

