

POLARA INX PUSH BUTTON

SPECIFICATIONS

POWER	10VDC to 24VDC
PUSH BUTTON	ADA compliant. Field adjustable directional arrow is standard; Bidirectional and blank buttons available. Optional adjustable locator tone
ACTIVATION CONFIRMATION	Yellow LEDs and voice confirmation activated when push button is pressed; custom message available
PUSH BUTTON HOUSING	Yellow powder coat finish is standard; black and green available
SPEAKER	Field replaceable, weather resistant, 10-watt audio amplifier Maximum volume: 100 dB at 1 meter
INSTRUCTIONAL SIGN	9 in. W x 12 in. H is standard (larger signs available); Signs available with braille; Retroreflective sheeting with tamper-resistant mounting screws
OPERATING FORCE	3 adjustable settings: 0.5 lb to 3.5 lbs
IDLE CURRENT DRAW	~9mA at 12VDC
PEAK CURRENT DRAW	~500mA (at 15VDC) with voice message at maximum
ENCLOSURE	NEMA 250 Type 4X Powdercoated cast aluminum cover and backplate
CONNECTIVITY	Bluetooth 5.0 Polara Field Service app for customization
WIRING	6 conductor
OPERATING TEMPERATURE RANGE	-30° F to 165° F (-34° C to 74° C)
DIMENSIONS	9" W x 18.2" L x 2.6" H

