

# POLARA INX PUSH BUTTON

## SPECIFICATIONS

<b>POWER</b>	10VDC to 24VDC
<b>PUSH BUTTON</b>	ADA compliant. Field adjustable directional arrow is standard; Bidirectional and blank buttons available. Optional adjustable locator tone
<b>ACTIVATION CONFIRMATION</b>	Yellow LEDs and voice confirmation activated when push button is pressed; custom message available
<b>PUSH BUTTON HOUSING</b>	Yellow powder coat finish is standard; black and green available
<b>SPEAKER</b>	Field replaceable, weather resistant, 10-watt audio amplifier Maximum volume: 100 dB at 1 meter
<b>INSTRUCTIONAL SIGN</b>	9 in. W x 12 in. H is standard (larger signs available); Signs available with braille; Retroreflective sheeting with tamper-resistant mounting screws
<b>OPERATING FORCE</b>	3 adjustable settings: 0.5 lb to 3.5 lbs
<b>IDLE CURRENT DRAW</b>	~9mA at 12VDC
<b>PEAK CURRENT DRAW</b>	~500mA (at 15VDC) with voice message at maximum
<b>ENCLOSURE</b>	NEMA 250 Type 4X Powdercoated cast aluminum cover and backplate
<b>CONNECTIVITY</b>	Bluetooth 5.0 Polara Field Service app for customization
<b>WIRING</b>	6 conductor
<b>OPERATING TEMPERATURE RANGE</b>	-30° F to 165° F (-34° C to 74° C)
<b>DIMENSIONS</b>	9" W x 18.2" L x 2.6" H

