

LEGENDVIZ® BLINKERSIGN®


SPECIFICATIONS

POWER	6VDC - 12VDC or low voltage; current controlled through TAPCO controller
SIGN LEGEND	Various MUTCD-compliant options available (R5-1a shown)
SIGN SUBSTRATE	0.080" highway-grade aluminum; perforated legend
REFLECTIVE SHEETING	3M™ translucent DG3; anti-graffiti overlay
ILLUMINATION	Legend: Dusk-to-dawn or vehicle-activated nighttime illumination Perimeter: 24/7, Dusk-to-Dawn or activated
LED TYPE	Legend: Environmentally protected, efficient 0.5-watt Perimeter: Environmentally sealed, high-power, 1-watt LED
LED COLOR	Legend: White (6500K) Perimeter: Red
LED QUANTITY	Legend: Variable to achieve illumination uniformity Perimeter: 8 LEDs
LED LIFE EXPECTANCY	Legend: 50,000 hours Perimeter: 100,000 hours
LED VISIBILITY	Legend: Nighttime viewable up to 500 feet and readable up to 300 feet Perimeter: Daytime viewable more than 1,000 feet and nighttime viewable more than 1 mile
OFFSET LEGEND LEGIBILITY	Illuminated sign legible without retroreflectivity or headlights; legible at twice the distance of standard signs*
PERIMETER DIMMING	Variable based on photocell sensor input or 6V solar panel
PERIMETER FLASH PATTERN	Various MUTCD-compliant options dependent upon sign legend
LED WIRING PROTECTION	Legend: Protected by sealed aluminum enclosure Perimeter: Protected by aluminum channel
MOUNTING BRACKETS	Universal mounting brackets included
MOUNTING HARDWARE	Various options included
OPERATING TEMPERATURE RANGE	-40°F to 122°F (-40°C to 50°C)
DIMENSIONS	Stop (R1-1): 30" L x 30" W, 36" L x 36" W Wrong Way (R5-1a): 42" L x 30" W Do Not Enter (R5-1): 30" L x 30" W, 48" L x 48" W (shown)

* According to the results of a closed-course driver trial and statistical analysis conducted by the Texas A&M Transportation Institute (TTI).



FRONT



BACK